



DECLARATION OF PERFORMANCE

GX-01-0037-03

1. Unique identification code of the product type

GUTEX Thermowall 5in1

2. Purpose of use

Thermal insulation for buildings

3. Manufacturer

**GUTEX Holzfaserplattenwerk
H. Henselmann GmbH + Co KG
Gutenberg 5
79761 Waldshut-Tiengen
Germany**

4. Authorised representative

No authorised representative

5. System for the assessment and verification of constancy of performance

System 3

6. Harmonised standard

EN 13171:2012+A1:2015

Notified body: NB 0672 - MPA Stuttgart

7. Declared performance

Essential features	stated as	Performance
Thermal resistance	Thermal resistance R_D per nominal thickness d_N	see table below 1)
	Nominal thermal conductivity λ_D [W/mK]	0,040
	Tolerance class	T5
Reaction to fire	Fire reaction Euro Class as per EN 13501-1	E
Durability of fire behaviour under the influence of heat, weathering, ageing/degradation	Properties of durability	NPD
Durability of the thermal resistance under the influence of heat, weathering, ageing/degradation	Thermal resistance R_D per nominal thickness d_N	NPD
	Thermal conductivity λ_D [W/mK]	NPD
	Properties of durability	NPD
	Dimensional stability	DS(70,-)3
Compressive strength	Compressive stress	CS(10/Y)100
	Point load	NPD
Tensile / flexural strength	Tensile strength perpendicular to the panel plane	TR10
	Tensile strength parallel to the panel plane	NPD
Durability of compressive strength under the influence of ageing/degradation	Creep behaviour under compressive stress	NPD
Water permeability	Short-term water absorption	WS1,0
Water vapour permeability	Water vapour transmission	MU4
Impact sound transmission (for floors)	Dynamic stiffness	NPD
	Thickness	NPD
	Compressibility	NPD
	Air flow resistivity	AF_r 60
Sound absorption level	Sound absorption	NPD
airborne sound insulation index	Air flow resistivity	AF_r 60
Release of dangerous substances, discharge into the building interior	Release of dangerous substances	NPD
smoldering behavior	smoldering behavior	NPD

NPD: No Performance Determined

1) Thermal resistance per panel thickness									
Thickness d_N [mm]	40	60	80	100	120	140	160	180	200
R_D [m ² K/W]	1,00	1,50	2,00	2,50	3,00	3,50	4,00	4,50	5,00

The performance of the above product corresponds to the declared performances.

The manufacturer named above is solely responsible for preparing the declaration of performance in accordance with Regulation (EU) No. 305/2011.

Signed for the manufacturer and on behalf of the manufacturer


GUTEX Holzfaserplattenwerk
H. Henselmann GmbH + Co KG
Gutenburg 5 · Tel.: 07741/6099-0
D-79761 Waldshut-Tiengen

Waldshut-Tiengen, 21/07/2025 · Claudio Thoma, Managing Director

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland