



Technical data

	Substance	
Protective and covering fleece	Polypropylene microfibre	
Membrane	monolithic TEEE	
Adhesive	special pressure sensitive acrylic adhesive	
Release film	silicone-coated PE film, split 25/125 cm	
Attribute	Regulation	Value
Colour		dark blue
Surface weight	BS EN 1849-2	240 g/m ²
Thickness	BS EN 1849-2	0.70 mm
Water vapour resistance factor μ	BS EN ISO 12572	570
sd-value	BS EN ISO 12572	0.40 m
sd-value humidity variable	BS EN ISO 12572	0.3 - 0.8 m
g-value		2.0 MN-s/g
g-value humidity variable		1.5 - 4 MN-s/g
Fire rating	BS EN 13501-1	E
Exposure time		3 months
Protection against outdoor exposure during construction for wooden frame structures/CLT ceilings		14 days
Water column	BS EN ISO 811	10 000 mm
Water tightness non-aged/aged*	BS EN 1928	W1 / W1
Airtightness		passed
Tensile strength MD/CD	BS EN 13859-1 (A) / -2 (A)	250 N/5 cm / 200 N/5 cm
Tensile strength MD/CD aged*	BS EN 13859-1 (A) / -2 (A)	190 N/5 cm / 160 N/5 cm
Elongation MD/CD	BS EN 13859-1 (A) / -2 (A)	70 % / 70 %
Elongation MD/CD aged*	BS EN 13859-1 (A) / -2 (A)	40 % / 50 %
Nail tear resistance MD/CD	BS EN 13859-1 (B) / -2 (B)	170 N / 220 N
*) Artificial ageing by long term at 100 °C ; 212 °F	BS EN 1297 / BS EN	passed
Flexibility at low temperature	BS EN 1109	-40 °C ; -40 °F
Temperature resistance		permanent -40 °C to 100 °C ; -40 °F to 212 °F
Thermal conductivity		2.3 W/(m·K)
Roof lining membrane	ZVDH Produktdatenblatt	UDB-A
Temporary roof covering; suitable as ...	ZVDH	yes
CE labelling	BS EN 13859-1/-2	available



Area of application

Allows airtightness to be created on wood-based products and mineral substrates – e.g. on the exterior side of unplastered (fair-faced) masonry or concrete components with joints.

Thanks to its full-surface adhesion, the membrane provides temporary protection for intermediate ceilings and floors on multi-storey CLT (cross-laminated timber) or wooden-frame buildings during the construction period. It also protects wall elements and roof structures with a roof pitch of greater than 14° for a period of up to 3 months.

In addition, it fulfils the requirements of the Central Association of the German Roofing Trade (ZVDH) for temporary coverings on roofs for the specified time period.

The information provided is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Ecological Building Systems

For stock information and full technical support for your project, please contact Ecological Building Systems or visit www.EcologicalBuildingSystems.com



info@EcologicalBuildingSystems.com

Ireland: 046 9432104 Fax: 046 9432435 UK: 01228 711 511 Fax: 01228 712 280

Forms of delivery

Art. no.	GTIN	Length	Width	Contents	Weight	Sales unit	Container
1AR01513	4026639215130	30 m	1.5 m	45 m ²	12 kg	1	24

Advantages

- ✓ Protects the structure: Diffusion-permeable and maximum protection against driving rain
- ✓ Keeps building components dry by means of a pore-free moisture-active functional membrane
- ✓ Easy and reliable installation thanks to its split release film
- ✓ Sticks immediately to subsurfaces with sufficient load-bearing capacity
- ✓ Permanent protection thanks to the high resistance to ageing and heat of the TEEE membrane
- ✓ 3 months of outdoor exposure

Substrates

Clean subsurfaces before sticking.

Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on materials to be bonded. Subsurfaces must be sufficiently dry and stable.

Bonding and joints are possible on planed and painted wood, hard plastics and metal (e.g. pipes, windows etc.), hard wood-based panels (chipboard, OSB, plywood, MDF and wood fibre underlay panels) and mineral subsurfaces such as concrete, non-plastered masonry or plaster.

Pretreatment with TESCON PRIMER is required in the case of adhesion to wood-fibre underlay panels. Concrete or plaster subsurfaces must not be sandy or crumbling.

It is your responsibility to check the suitability of the subsurface; adhesion tests are recommended in certain cases. Pretreatment with TESCON PRIMER is necessary in the case of subsurfaces with insufficient stability.

General conditions

SOLITEX ADHERO is to be installed with the printed side facing the installation technician; it can be installed on stable subsurfaces (e.g. OSB, chipboard, MDF, plywood sheets, wood fibre underlay panels, layers of plaster (e.g. gypsum, lime, lime cement), masonry, concrete etc.). The membranes can be installed on walls either vertically or horizontally in an overlapping, waterproof manner. If significant rain loads are expected (e.g. in roof areas or on walls with high loads of driving rain), horizontal waterproof installation is recommended.

To achieve airtight installation, membranes must be installed with no folds or creases. When installing the membranes, rub them firmly into place using PRESSFIX XL.

SOLITEX ADHERO can provide temporary protection for intermediate ceilings and floors on multi-storey CLT (cross-laminated timber) or wooden-frame buildings during construction for a period of up to 14 days.

It can also be used on exterior walls.

Additionally, it can be used as a temporary covering for up to 3 months to protect inclined roofs with a roof pitch of greater than 14° in accordance with the regulations of the Central Association of the German Roofing Trade (ZVDH).

In addition, system components such as the TESCON NAIDECK nail sealing tape and the KAFLEX / ROFLEX pipe and cable grommets are to be used. The specifications in the regulations of the German Roofing Trade are to be taken into account when carrying out installation and adhesion.



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Ecological Building Systems

For stockist information and full technical support for your project, please contact Ecological Building Systems or visit www.EcologicalBuildingSystems.com



Ireland: 046 9432104 Fax: 046 9432435 UK: 01228 711 511 Fax: 01228 712 280

info@EcologicalBuildingSystems.com