SOLITEX FRONTA® WA

Breather membrane (WRB)



Technical data

	Material
Protective and covering fleece	Polypropylene microfibre
Functional film	Monolithic TEEE

Property	Regulation	Value		
Colour		Black		
Surface weight	BS EN 1849-2	100 g/m ²		
Thickness	BS EN 1849-2	0.45 mm		
Water vapour resistance factor μ	BS EN ISO 12572	110		
sd value	BS EN ISO 12572 0.05 m			
g value		0.25 MN·s/g		
Fire class	BS EN 13501-1	E		
Outdoor exposure		3 months		
Watertight joints with 'connect' adhesive strips or TESCON VANA tape	BS EN 13859-1	W1		
Water column	BS EN ISO 811	10 000 mm		
Watertightness, non-aged/aged*	BS EN 13859-2	W1 / W1		
Tensile strength MD/CD	BS EN 13859-2 (A)	210 N/5 cm / 140 N/5 cm		
Tensile strength MD/CD, aged*	BS EN 13859-2 (A)	190 N/5 cm / 120 N/5 cm		
Elongation MD/CD	BS EN 13859-2 (A)	85% / 85%		
Elongation MD/CD, aged*	BS EN 13859-2 (A)	70% / 70%		
Nail tear resistance MD/CD	BS EN 13859-2 (B)	110 N / 140 N		
*) Durability after artificial ageing	BS EN 1297 / BS EN 1296	Passed		
Flexibility at low temperature	BS EN 1109	-40 °C ; -40 °F		
Temperature resistance	EN 1109, EN 1296, EN 1297	Permanent -40 °C to 100 °C ; -40 °F to 212 °F		
Thermal conductivity	·	0.04 W/(m·K)		
CE labelling	BS EN 13859-2	Yes		

Areas of application

For use as a breather membrane (weather-resistive barrier, WRB) behind closed facades. Installation over sheathing, wood-based panels and all mat or panel-shaped thermal insulation materials.

Supply form

Art. no.	Length	Width	Contents	Weight	Sales unit	Container	GTIN
10132	50 m	1.5 m	75 m²	7.5 kg	1	20	4026639010612
10133	50 m	3 m	150 m²	15 kg	1	20	4026639010605

Advantages

- ✓ Very robust: strong, 3-ply structure
- ✓ Dry building structures: pore-free TEEE functional film actively transports moisture to the outside
- ✓ Easy to work with: high nail pull-out resistance
- ✓ For use behind closed facades
- ✓ 3 months of outdoor exposure

General conditions

SOLITEX FRONTA WA membranes are to be installed horizontally in a taut manner with no sagging.

The membrane must not be secured in areas where water collectively drains off.

The membrane can be used behind closed facades with at least 20 mm of rear ventilation.

Additional measures (e.g. covering with tarpaulins) should be taken during the construction phase in the case of buildings that are lived in or buildings that are to be given particular protection. Covering with tarpaulins should also be considered if construction work is to be interrupted for a longer period.













The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the proclima planning documentation and application recommendations. If you have any questions, please call the pro-clima technical hotline Ireland and UK:

Phone: +353 46 9432104 Fax: +353 46 9432435

info@ecologicalbuildingsystems.com

For Stockists contact

Ireland

Phone: +353 (0)46 9432104 Fax: +353 (0)46 9432435

UK

Phone: +44 (0)1228 711 511 Fax: +44 (0)1228 712 280

Ecological Building Systems

 $in fo@ecological building systems. com\\www.ecological building systems. com$

MOLL bauökologische Produkte GmbH

Rheintalstraße 35 - 43 68723 Schwetzingen Germany www.proclima.com



For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland

