SOLITEX FRONTA® WA

Breather membrane (WRB)



Technical data

	Material
Protective and covering fleece	Polypropylene microfibre
Functional film	Monolithic TEEE

Property	Regulation	Value
Colour		Black
Surface weight	BS EN 1849-2	100 g/m²
Thickness	BS EN 1849-2	0.45 mm
Water vapour resistance factor μ	BS EN ISO 12572	110
sd value	BS EN ISO 12572	0.05 m
g value	BS EN ISO 12572	0.25 MN·s/g
Reaction to fire classification	BS EN 13501-1	E
Outdoor exposure		3 months
Watertight joints with 'connect' adhesive strips or TESCON tape	BS EN 13859-1	W1
Water column	BS EN ISO 811	10 000 mm
Watertightness, non-aged/aged*	BS EN 13859-2	W1 / W1
Tensile strength MD/CD	BS EN 13859-2 (A)	210 N/5 cm / 140 N/5 cm
Tensile strength MD/CD, aged*	BS EN 13859-2 (A)	190 N/5 cm / 120 N/5 cm
Elongation MD/CD	BS EN 13859-2 (A)	85% / 85%
Elongation MD/CD, aged*	BS EN 13859-2 (A)	70% / 70%
Nail tear-resistance MD/CD	BS EN 13859-2 (B)	110 N / 140 N
*) Durability after artificial ageing	BS EN 1297 / BS EN 1296	Passed
Foldability at low temperature	BS EN 495-5	-50 °C
Temperature resistance, permanent	EN 495-5, EN 1296, EN 1297	-50 °C to 100 °C
Thermal conductivity		0.04 W/(m·K)
Resistance to alkalis	BS EN 1847	Passed
CE labelling	BS EN 13859-2	Yes

Areas of application

For use as a breather membrane (weather-resistive barrier, WRB) behind closed facades. Installation over sheathing, wood-based panels and all mat or panel-shaped thermal insulation materials.

Supply forms

Art. no.	Length	Width	Contents	Weight	Sales unit	Container	GTIN
10132	50 m	1.5 m	75 m²	7.5 kg	1	20	4026639010612
10133	50 m	3 m	150 m²	15 kg	1	20	4026639010605

Advantages

- ✔ Very robust: strong, 3-ply structure
- ✔ Dry building structures: pore-free TEEE functional film actively transports moisture to the outside
- ✔ Easy to work with: high nail pull-out resistance
- ✔ For use behind closed facades
- ✔ 3 months of outdoor exposure

General conditions

SOLITEX FRONTA WA membranes are to be installed horizontally in a taut manner with no sagging.

The membrane must not be secured in areas where water collectively drains off.

The membrane can be used behind closed facades with at least 20 mm of rear ventilation.

Additional measures (e.g. covering with tarpaulins) should be taken during the construction phase in the case of buildings that are lived in or buildings that are to be given particular protection. Covering with tarpaulins should also be considered if construction work is to be interrupted for a longer period.

EPD verified

NBS

NSAI Agrément
Solitex Fronta WA Breathable Wall Protection Membrane
CERT No. 04/0210

CE
07
EN 13859-2

UK CA

Made in Germany developed and produced by pro clima

The applications and conditions described here are based on current research findings and practical experience. We reserve the right to change the recommended application designs and installation methods and to develop and thus change the properties and quality of individual products. We would be glad to inform you about the current state of engineering knowledge at the time that your installation is carried out.

The planning documentation that is available from pro clima provides further information about installation methods and design details. If you have questions, please contact pro clima Technical Support in Ireland and the UK:
Phone: +353 46 9432104
info@ecologicalbuildingsystems.com

To find your local stockist, please contact:

Ireland
Phone: +353 46 9432104

UK
Phone: +44 1228 711 511

Ecological Building Systems
info@ecologicalbuildingsystems.com
www.ecologicalbuildingsystems.com

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
68723 Schwetzingen
Germany
www.proclima.com

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.

Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104

Email us

info@ecologicalbuildingsystems.com

Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland

ecological BUILDING SYSTEMS

Discover our solutions online at

ecologicalbuildingsystems.com