

Waterproof sealing tape, for interior and exterior use



Technical data

	Material
Backing	Elastic PE carrier film
Main component	Butyl rubber modified with acrylate
Release film	Silicone-coated PE film

Property	Regulation	Value		
Colour		Butyl rubber: grey; film: black		
Surface weight	BS EN 1849-2	1.9 kg/m²		
Thickness	BS EN 1849-2	1.1 mm		
sd value	BS EN 1931	> 200 m		
g value		> 1 000 MN·s/g		
Outdoor exposure		6 months		
Resistance to driving rain	Innovation Center Iceland	Up to 2400 Pa, around window		
Resistance to driving rain	ift, MO-01/1:2007-01, Abs. 5	Up to 600 Pa, sub-sill flashing		
Application temperature		-10 °C to 35 °C ; 14 °F to 95 °F		
Temperature resistance		Permanent -40 °C to 80 °C		
Storage		Cool and dry		

Areas of application

For creating a sub-sill, for sealing window joints with masonry or concrete structures, for sealing wood-based panels to smooth mineral surfaces, for taping underlay panels made of wood fibre to one another (e.g. in roof valleys and transitions), and for sealing these to adjoining structural elements.

Splits on release film

(Note: inch conversions are approximate)

Tape width Split (approx.)

100 mm 25 | 75 mm 150 mm 25 | 65 | 60 mm 200 mm 25 | 115 | 60 mm 300 mm 25 | 155 | 120 mm

Supply form

Art. no.	GTIN	Length	Width	Splits on release film	Weight	Sales unit	Container
15361	4026639153616	20 m	100 mm	25 75 mm	3.5 kg	3	180
14134	4026639141347	20 m	150 mm	25 65 60 mm	5.3 kg	2	120
14135	4026639141354	20 m	200 mm	25 115 60 mm	6.9 kg	2	84
14732	4026639147325	20 m	300 mm	25 155 120 mm	10.5 kg	1	60

Advantages

- $\begin{tabular}{ll} \hline \end{tabular} \begin{tabular}{ll} \textbf{Excellent protection for building structures thanks to strong sealing effect} \\ \hline \end{tabular}$
- ✓ Reliable application: extremely high adhesive strength even to slightly damp and cold subsurfaces
- ✓ Easy to work with: very elastic can adapt flexibly to subsurfaces and corners
- ✓ Proven resistance to driving rain up to 2400 Pa
- ✓ Independently confirmed suitability: tests in accordance with MO-01/1 passed at IFT in Rosenheim, Germany
- ✓ Subsequent work can be started quickly: adheres to stable mineral subsurfaces without primers
- ✓ Excellent values in hazardous substance testing, has been tested according to the ISO 16000 evaluation scheme

Substrates

Clean subsurfaces before sticking. Adhesion is not possible on frozen surfaces. There must be no water-surfaces substances (e.g. grease or silicone) on surfaces where adhesives are to be applied. Subsurfaces must be sufficiently dry and stable.

Permanent adhesion is achieved on all pro clima interior and exterior membranes, on other vapour control and airtight membranes (e.g. those made of PE, PA, PP and aluminium) and on other underlay and breather (WRB) membranes (e.g. those made of PP and PET). Adhesive bonds are possible with planed and painted wood, hard plastics and metal (e.g. pipes, windows etc.), hard wood-based panels (chipboard, OSB, plywood, MDF and wood-fibre underlay panels) and mineral subsurfaces such as concrete, unplastered masonry or plaster.



Data sheet EXTOSEAL ENCORS

Pre-treatment with TESCON PRIMER is required in the case of adhesion to wood-fibre underlay panels. Concrete or plaster subsurfaces must not be sandy or crumbling. Pre-treatment with TESCON PRIMER is recommended in the case of subsurfaces that have insufficient stability.

The best results in terms of reliability are achieved on high-quality subsurfaces. It is your responsibility to check the suitability of the subsurface; adhesion tests may be necessary in certain cases.

General conditions

Adhesive bonds must not be subjected to tensile forces. Rub the adhesive tapes firmly to secure the adhesive bonds. Ensure that there is sufficient resistance pressure. Windproof, airtight or rainproof sealing can only be achieved on vapour control or underlay/facade membranes that have been installed without folds or creases. The tape is self-sealing under the effect of heat.



Prüfbericht Nr. 16–000527–PR02 (PB 2–E03–020310-de–01) Unterfensterbank EXTOSEAL ENCORS mit CONTEGA SOLIDO EXO nach MO–01/1:2007–01, Abs. 5 24.06.2016







The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and IIK.

Phone: +353 46 9432104 Fax: +353 46 9432435

info@ecologicalbuildingsystems.com

For Stockists contact

Ireland

Phone: +353 (0)46 9432104 Fax: +353 (0)46 9432435

UK

Phone: +44 (0)1228 711 511 Fax: +44 (0)1228 712 280

Ecological Building Systems

info@ecologicalbuildingsystems.com www.ecologicalbuildingsystems.com

MOLL bauökologische Produkte GmbH

Rheintalstraße 35 - 43 68723 Schwetzingen Germany www.proclima.com



For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland

