



Technical data

Material		
Main component	SOLID acrylate, no plasticisers, solvents, emulgators or preservatives	
Release film	Silicone-coated PP film	
Property	Regulation	Value
Colour		Translucent green
Width of adhesive bead		11 mm
Thickness of adhesive bead		3 mm
Moisture resistance		Waterproof
Bond durability, non-aged/ aged	DIN 4108-11 / EN 17990	Passed
Adhesion	BS EN 1939	16 N/cm
Application temperature		Above -15 °C ; 5 °F
Temperature resistance		Permanent -40 °C to 100 °C ; -40 °F to 212 °F
Storage		Horizontal, cool and dry, protect from direct sunlight

Areas of application

Solvent-free, permanent, elastic, frost-resistant airtight adhesive that is applied from a roll, for sealing all types of vapour control membranes and vapour barriers – e.g. INTELLO, INTELLO X, DB+, DASATOP and DA, as well as PE, PA, PP or aluminium sheeting – to mineral or rough adjacent components such as masonry, plasterwork, concrete or roughly sawn wood.

Creation of windtight seals for typical commercially available roofing underlay membranes (e.g. those made of PP or PET). Sealed joints with the SOLITEX MENTO series, SOLITEX QUANTHO, SOLITEX ADHERO and SOLITEX UM meet the requirements of the German ZVDH product data sheets.

Creation of windtight seals for breather membranes of all kinds (e.g. SOLITEX FRONTA series).

Supply form

Art. no.	Length	Width	Contents	Weight	Sales unit	Container	GTIN
1AR02195	10 m	11 mm	2 rolls	0.769 kg	6	630	4026639221957

Advantages

- ✓ Subsequent work can be started quickly: adhesive sealant from a roll, no drying time – joint can be subjected to loading immediately
- ✓ Can be used flexibly: sticks in a permanent, reliable manner thanks to water-resistant SOLID adhesive
- ✓ Reliable even during frosty conditions: sticks reliably above -15 °C
- ✓ Construction in adherence with standards: for airtight sealing in accordance with DIN 4108-7, SIA 180 and RE 2020
- ✓ Excellent values in hazardous substance testing, has been tested according to the ISO 16000 evaluation scheme

Substrates

Clean subsurfaces before applying adhesive. Mineral surfaces (plaster or concrete) may be slightly moist. Adhesion is not possible on frozen surfaces. There must be no water-repellent substances (e.g. grease or silicone) on surfaces to be sealed. Subsurfaces must have sufficient stability – if necessary, a mechanical support (pressure lath) must be used (e.g. on crumbling subsurfaces).

Permanent adhesion is achieved on all pro clima interior and exterior membranes, on other vapour control and airtight membranes (e.g. those made of PE, PA, PP and aluminium) and on other underlay and breather membranes (e.g. those made of PP and PET). Seals can be created on mineral subsurfaces (e.g. plaster or concrete), roughly sawn, planed or painted wood, hard plastics or rustproof metal (e.g. pipes, windows etc.) and hard wood-based panels (chipboard, OSB, plywood, MDF panels).

The best results in terms of achieving a well-protected structure are achieved on high-quality subsurfaces. It is your responsibility to check the suitability of the subsurface; adhesion tests may be necessary in certain cases. Pre-treatment with TESCON PRIMER is recommended in the case of subsurfaces that have insufficient stability.

General conditions

The adhesive joints created must not be subjected to tensile forces. It may be advisable to implement protective measures such as mechanical reinforcements in the case of subsurfaces that have insufficient stability. Rub the tape firmly into place (e.g. using the PRESSFIX application tool). Ventilate continuously and systematically to prevent build-up of excessive humidity; use a dryer if necessary. The product achieves its final level of strength after approx. 24 h.

Tested for hazardous
substances according to



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:

Phone: +353 46 9432104

Fax: +353 46 9432435

info@ecologicalbuildingsystems.com

For Stockists contact

Ireland

Phone: +353 (0)46 9432104

Fax: +353 (0)46 9432435

UK

Phone: +44 (0)1228 711 511

Fax: +44 (0)1228 712 280

Ecological Building Systems

info@ecologicalbuildingsystems.com

www.ecologicalbuildingsystems.com

MOLL bauökologische Produkte GmbH

Rheintalstraße 35 - 43

68723 Schwetzingen

Germany

www.proclima.com

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland