

# INSTAABOX

## Installation box



### Technical data

Material	
Main component	polyethylene, flexible and extensible

Property	Regulation	Value
Colour		Translucent
Length/width service cavity		260 mm / 130 mm
Length/width total		320 mm / 190 mm
Depth		55 mm
Cable diameter		max. 20 mm
sd value	BS EN 1931	> 10 m
g value		> 50 MNs/g
Reaction to fire classification	BS EN 13501-1	E
Temperature resistance		Permanent -10 °C to 80 °C ; 14 °F to 176 °F
Storage		Cool and dry

### Areas of application

For structures without dry lining, the INSTAABOX can create space for junction boxes and the like. It is attached and sealed so that it is airtight to the existing vapour-controlling and airtightness layer. It complies with the requirements of DIN 4108-7, SIA 180 and RE 2020 with regard to airtightness when using conventional junction boxes. The INSTAABOX can be used for both internal and external walls.

The INSTAABOX is oversized to prevent the airtight sealing layer being damaged if holes need to be drilled for the junction boxes.

### Supply form

Art. no.	Length	Width	Contents	Weight	GTIN
1AR02160	320 mm	190 mm	10 pieces	0.26 kg	4026639221605

### Advantages

- ✓ For cables and conduits up to 20 mm in diameter
- ✓ Construction in adherence with standards: for airtight sealing in accordance with DIN 4108-7, SIA 180 and RE 2020
- ✓ Provides space for up to three junction boxes
- ✓ Can be extended at will by cutting and sticking together again
- ✓ Excellent values in hazardous substance testing, has been tested according to the ISO 16000 evaluation scheme

### Substrates


The INSTAABOX can be used on all common airtight substrates used in construction. Recommendations on suitable sealants for connecting it to the airtight sealing layer (e.g. vapour control, wood-based panels or mineral substrate) is given in the [pro clima application matrix](#).

Further information can be found in the technical data sheets provided with the sealant.

### General conditions

The adhesive bonds should not be subjected to tensile strain. When the vapour control membrane is sealed, the weight of the insulating material must be borne by lathing. Adhesion should be supported by additional laths, if necessary.

Rub the adhesive tapes firmly to secure the adhesive bonds. Ensure that there is sufficient resistance pressure. Airtight seals can only be achieved on vapour control membranes that have been laid without folds or creases. Ventilate continuously and systematically to prevent the build-up of excessive humidity; use a dryer if necessary.



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

Tested for hazardous substances according to



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:

Phone: +353 46 9432104

Fax: +353 46 9432435

[info@ecologicalbuildingsystems.com](mailto:info@ecologicalbuildingsystems.com)

#### For Stockists contact

##### Ireland

Phone: +353 (0)46 9432104

Fax: +353 (0)46 9432435

##### UK

Phone: +44 (0)1228 711 511

Fax: +44 (0)1228 712 280

#### Ecological Building Systems

[info@ecologicalbuildingsystems.com](mailto:info@ecologicalbuildingsystems.com)

[www.ecologicalbuildingsystems.com](http://www.ecologicalbuildingsystems.com)

#### MOLL bauökologische Produkte GmbH

Rheintalstraße 35 - 43

68723 Schwetzingen

Germany

[www.proclima.com](http://www.proclima.com)

---

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

**As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.**



**Call us**

**Great Britain** +44 (0)1228 711511

**Ireland** +353 46 9432104



**Email us**

[info@ecologicalbuildingsystems.com](mailto:info@ecologicalbuildingsystems.com)



**Find us**

**Great Britain** Ecological Building Systems UK Ltd.,  
Cardewlees, Carlisle, Cumbria, CA5 6LF,  
United Kingdom

**Ireland** Ecological Building Systems Ltd.,  
Main Street, Athboy. Co. Meath, C15 Y678,  
Republic of Ireland