

Declaration of performance 0068 - CPR - 022/2014 - DP116EN1634200

- 1. Unique identification code of the product-type: Decork
- 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Product name: Decork

Production date and batch are printed on the package.

Production plant: Diasen Srl - zona Ind.le Berbentina, 5 – 60041 Sassoferrato (AN).

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Products and systems for the protection and restoration of concrete structures – Part 2 : Systems to protect concrete surfaces in compliance with UNI EN 1504-2.

Intended use: products for protecting surfaces -coating. Intended employment: damp control and increase of resistivity. Product used in buildings and civil engineer works.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 (5):

Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN) - www.diasen.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):

Not applicable.

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+.

7. In case of a declaration of performance concerning a construction product covered by a harmonized standard Istituto di Ricerche e Collaudi M. Masini – Identification number: 0068.

Has done:

- 1. initial inspection of the production plant and production control;
- supervision, assessment and evaluation of plant production control. According to system 2+ and issued the certificate of conformity of the plant production control num 0068-CPR-022/2014 of 27th/03/2014.
- 8. Declared performance:

Essential Characteristics	Performance	Test methodology
Water vapour permeability	μ = 15	UNI EN ISO 7783
Capillary absorption and water permeability	NPD	UNI EN 1062-3
Adhesion test for direct traction	NPD	UNI EN 1542
Thermal conductivity	λ = 0.086 W/mK	UNI EN 12667
Reaction to fire	NPD	UNI EN 13501-1
Dangerous substances	See safety data sheet	EC Regulation n. 1272/2008

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: Diego Mingarelli – Legal representative Sassoferrato, 23th/08/2016

R04_7.2_QEMS rev 0 of 30th/06/2013

Member of CISQ Federation

DiaSen srl Z. Ind.le Berbentina, 5









Zona Industriale Berbentina, 5 – 60041 Sassoferrato (AN) – Italy ww.diasen.com

14 CPR – 022/2014 UNI EN 1504-2 DECORK

Products and systems for the protection and restoration of concrete structures – Part 2: Systems to protect concrete surfaces

Water vapour permeability: $\mu = 15$ Capillary absorption and water permeability: NPD Adhesion Test for direct traction: NPD

Thermal conductivity: $\lambda = 0.086 \text{ W/mK}$

Reaction to fire: NPD

Dangerous substances: See safety data sheet



