

Technical data



| Technical data | | |
|-------------------------|------------|--|
| Main component | Material | Synthetic rubber |
| Property | Regulation | Value |
| Colour | | Translucent |
| Application temperature | | -5 °C to 40 °C ; 23 °F to 104 °F |
| Temperature resistance | | Permanent -25 °C to ~90 °C, short-term up to 100 °C (1h); °F: -13 to ~195; 212 |
| Coverage | | ~ 3.2 m ² /l |
| Storage | | 12 months, protect from frost, cool and dry |

Areas of application

For preparation and stabilisation of subsurfaces for subsequent application of pro clima adhesive tapes such as TESCON VANA, TESCON PROFECT and sealing tapes in the EXOSEAL series. Suitable for wood, wood-fibre boards, masonry, roofs, walls and ground slabs.

Coverage

| Delivery form | Content | Application width | Coverage |
|---------------|---------|-------------------|--------------|
| Spray can | 400 ml | 60 mm | ~20 m; 22 yd |
| | | 75 mm | ~17 m; 18 yd |
| | | 150 mm | ~9 m; 10 yd |
| Spray can | 750 ml | 60 mm | ~38 m; 41 yd |
| | | 75 mm | ~31 m; 34 yd |
| | | 150 mm | ~17 m; 18 yd |

The quantity used may vary depending on the substrate and application method.

Supply form

| Art. no. | Contents | Coverage | Weight | Sales unit | Container | GTIN |
|----------|----------|----------------------|----------|------------|-----------|---------------|
| 1AR01114 | 0.4 l | ~ 1.3 m ² | 0.39 kg | 12 | 1008 | 4026639211149 |
| 1AR01050 | 0.75 l | ~ 2.4 m ² | 0.695 kg | 6 | 336 | 4026639210500 |

Advantages

- ✓ Easy to apply: spray on directly from the can, no contamination of the primer in its container
- ✓ Secure bonds: penetrates deep and strengthens dusty subsurfaces or subsurfaces with insufficient stability
- ✓ Saves time: adhesive tapes can be applied to absorbent subsurfaces with no drying time necessary
- ✓ Flexible use: use on dry and slightly moist subsurfaces
- ✓ At any time of the year: can also be applied during frosty conditions

Substrates

Before primer is applied, clean the subsurfaces. Frozen and soaked subsurfaces are not suitable for the application of primer. There must be no water-repellent substances (e.g. grease or silicone) on the subsurface.

All mineral surfaces (e.g. plaster or concrete) and (used) timber subsurfaces can be pre-treated. It is also possible to strengthen porous materials such as wood-fibre underlay panels. Subsurfaces are to be checked for compatibility, if necessary.

Permeable absorbent subsurfaces (e.g. wood-fibre underlay panels) may be slightly moist. In this case, the adhesive tape to be used can be applied directly onto primer that is still wet. The product achieves its final level of strength only when it has dried. It may be advisable to use covers to protect the area that has been treated. Primer that has not yet fully dried must be protected against the effects of the weather. The amount of primer to be applied depends on the absorbency of the substrate; it is your responsibility to determine this.

If butyl rubber tapes (e.g. EXOSEAL range) that hinder diffusion are applied onto relatively well-sealed, non-absorbent subsurfaces (e.g. concrete), the primer must first be allowed to fully dry before the adhesive tape is put in place.

Only ORCON CLASSIC or ORCON MULTIBOND can be used when applying primer for adhesive sealants. The primer and ORCON CLASSIC must be fully dried (1-2 days) before the membrane material is stuck in place (dry process).

General conditions

Shake the can well before application. The fan-shaped spray jet can be adjusted in the horizontal and vertical directions by turning the spray head nozzle. After every spray application, spray the can upside down until only blowing agent comes out so as to avoid blocking the valve riser tube and the spray head with primer residues. Wipe off any primer at the outlet of the nozzle.

Spray the surface to be taped after cleaning it – spray distance 20 – 25 cm. Allow to ventilate for between 5 and 15 min. (depending on material and application). Repeat this procedure again for absorbent subsurfaces.



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:

Phone: +353 46 9432104
Fax: +353 46 9432435
info@ecologicalbuildingsystems.com

For Stockists contact

Ireland

Phone: +353 (0)46 9432104
Fax: +353 (0)46 9432435

UK

Phone: +44 (0)1228 711 511
Fax: +44 (0)1228 712 280

Ecological Building Systems

info@ecologicalbuildingsystems.com
www.ecologicalbuildingsystems.com

MOLL bauökologische Produkte GmbH

Rheintalstraße 35 – 43
68723 Schwetzingen
Germany
www.proclima.com

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland