



## [Clima Redboard Laibungsplatte]

**interior pre-primed mineral window soffit board  
made of calcium silicate**

### Areas of application:

- for use in areas around windows and door reveals and door reveals in interior spaces
- to compensate for thermal bridging
- prevents mould growth
- absorbs excess interior air humidity

### Features/benefits:

- primed on the room side (sanded on both sides)
- controls humidity
- capillary-active
- breathable
- heat-insulating
- mould-resistant
- non-flammable (A1)
- countless micropores
- natural raw materials
- environmentally friendly
- 'Made in Germany' quality

### Technical data:

- |                                   |  |
|-----------------------------------|--|
| • Material:                       | Calcium silicate, cellulose fibres   |
| • Fire behaviour:                 | Class A1 in accordance with<br>EN 13501-1:2010<br>(in keeping with ETA-19/0559)  |
| • Water vapour resistance factor: | $\mu = 3$  |
| • Thermal conductivity:           | $\lambda_D (23.50) = 0.059 \text{ W/(mK)}$<br>$\lambda_{\text{Rated value}} = 0.062 \text{ W/(mK)}$<br>(in keeping with ETA-19/0559) |
| • Apparent density range:         | 180-187 kg/m <sup>3</sup>  |
| • Pressure resistance:            | ≥ 1000 kPa   |
| • Water absorption coefficient:   | 46 kg/m <sup>2</sup> √h  |
| • pH value:                       | approx. 10   |

### Instructions for use:

The **Clima Redboard Window Soffit Board [Clima Redboard Laibungsplatte]** corresponds to **Clima Redboard pro** in terms of its structure and design. Thus, the same processing guidelines in relation to the subsoil preparation or underground quality, processing and surface coating apply.

The technical information and instructions for use contained in this document are correct to the best of our knowledge and are provided in good faith. The content of this document does not constitute an explicit or implicit guarantee for the performance of these products. As we have no control over how our materials will be used or the conditions under which they are used, we can only guarantee that these products meet our quality standards. We can therefore only guarantee the quality of our products within the framework of our General Terms and Conditions, but we cannot guarantee their successful functioning in every situation. Subject to changes without prior notice. This data sheet replaces all previous data sheets.



## [Clima Redboard Laibungsplatte]

---

Suitable substrates are, for example, load-bearing and levelled lime or lime-cement plasters. Mineral substrates may be damp, but not wet. Wallpaper, paints, loose components and filler layers containing gypsum must be removed.

Sustainable gypsum plasters must be dry and have a minimum thickness of 10 mm.

Mould infestations must be removed professionally. If it is necessary to disinfect the substrate, redstone **Mould and Spore Destroyer SuS** [Schimmelpilz- und Sporenvernichter SuS] from the Vivo Mould Remedy line [“Schimmelsanierung (Vivo)”] should be used. Building defects and penetrating moisture such as rising damp or driving rain must be remedied in advance with appropriate measures. Absorbent substrates must be pre-wetted or prepared with redstone **Primer** [Grundierung].

In general, **Clima Redboard Window Soffit Boards** [Clima Redboard Laibungsplatten] are glued without cavities and glued over the entire surface. The application of the adhesive (**System Adhesive** [Systemkleber] or, in the case of substrates containing gypsum: **Special Adhesive SB** [Spezialkleber SB]) is applied on the substrate always just for one board following the comb bed method (horizontal) using a notched trowel (at least 10 mm).

Uneven substrates should be levelled in advance using mineral patching plaster.

**Clima Redboard Window Soffit Boards** [Clima Redboard Laibungsplatten] are placed, for example, in the area around the window on the front side of the frame. To prevent cracks, it is recommended to insert redstone **Pre-Compressed Sealant Tape** [Komprimierband] into the connection joint. Decoupling to further adjacent building components such as floors and ceilings using redstone **Pre-Compressed Sealant Tape** [Komprimierband] is to be provided for.

In addition, corrosion-free corner protection rails (e.g. made from plastic or aluminium) should be used, which are fixed using **System Adhesive** [Systemkleber] or **Special Adhesive SB** [Spezialkleber SB]; if further fasteners are required, they must be made of non-rusting material.

Arched and vaulted reveals can be adapted using smaller segment strips and oblique sections.

From a room height above 3.50 m or for areas with increased load (e.g. tiles), the **Clima Redboard Window Soffit Boards** [Clima Redboard Laibungsplatten] must be attached in addition to gluing with **Clima plugs** [Clima Dübel].

### **Dimensions / Form of delivery / Article No. / EAN No.:**

250 x 500 x 15 mm / 20 pcs. per package / RBLI5250MM / 4260122563951

### **Other:**

The requirements of the EC Safety Data Sheet must be adhered to.

---

The technical information and instructions for use contained in this document are correct to the best of our knowledge and are provided in good faith. The content of this document does not constitute an explicit or implicit guarantee for the performance of these products. As we have no control over how our materials will be used or the conditions under which they are used, we can only guarantee that these products meet our quality standards. We can therefore only guarantee the quality of our products within the framework of our General Terms and Conditions, but we cannot guarantee their successful functioning in every situation. Subject to changes without prior notice. This data sheet replaces all previous data sheets.

---

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

**As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.**



**Call us**

**Great Britain** +44 (0)1228 711511

**Ireland** +353 46 9432104



**Email us**

[info@ecologicalbuildingsystems.com](mailto:info@ecologicalbuildingsystems.com)



**Find us**

**Great Britain** Ecological Building Systems UK Ltd.,  
Cardewlees, Carlisle, Cumbria, CA5 6LF,  
United Kingdom

**Ireland** Ecological Building Systems Ltd.,  
Main Street, Athboy. Co. Meath, C15 Y678,  
Republic of Ireland