



Technical data

Material	
Main component	Butyl rubber
Release film	Silicone-coated paper

Property	Regulation	Value
Colour		Black
Thickness		1.0 mm
Outdoor exposure		6 months, installed under the counter battens
Application temperature		5 °C to 35 °C ; 41 °F to 95 °F
Temperature resistance		Permanent -40 °C to 80 °C ; -40 °F to 176 °F
Storage		Cool and dry

Areas of application

Nail-sealing tape for use underneath counter battens for pitched roof structures. The use of nail-sealing tapes in combination with "underlay membranes with seam and perforation protection" (SOLITEX connect variants) is a required additional measure in the case of "more demanding requirements" (e.g. if the roof pitch is less than the standard roof pitch), according to the Central Association of the German Roofing Trade (ZVDH). If required, TESCON NAIDECK also serves as a suitable additional measure when creating a temporary covering.

Supply form

Art. no.	Length	Width	Weight	Sales unit	Container	GTIN
1AR02150	20 m	50 mm	1.375 kg	24	576	4026639221506
1AR02152	20 m	75 mm	2.06 kg	16	384	4026639221520

Advantages

- ✓ Very good sealing effect: sealing material is pulled into the hole created when a nail or screw is fitted
- ✓ Conforms to regulations: satisfies the requirements of the German ZVDH trade association and of the Swiss SIA 232/1 standard
- ✓ Provides protection during the construction period: suitable as a temporary covering

Substrates

Clean substrates before applying tape. Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on surfaces where adhesives are to be applied. Subsurfaces must be sufficiently dry and stable; if necessary, substrates should be stabilised or renewed.

Lasting nail-tightness is achieved on all pro clima exterior membranes and other underlay and breather (WRB) membranes (e.g. those made of PP and PET) as well as MDF board and wood-fibre sub-roof panels.

The best results in terms of reliability are achieved on high-quality substrates. Particular care is necessary when working with older or multi-layer substrates. It is your responsibility to check the suitability of the substrate; adhesion tests may be necessary in certain cases. Pre-treatment of the substrate with TESCON PRIMER will improve the adhesive bond.

General conditions

Perforation seals and water-resistant adhesive joints will only be effective on roofing underlay membranes that have been installed with no folds or creases. Install TESCON NAIDECK continuously between the counter battens and the roofing underlay membrane. This will ensure that any perforations that are created when the roof battens are being fastened will also be sealed. This tape can be applied onto the counter batten or the substrate that is to be sealed. Rub the tape firmly to secure the adhesive bond. Daytime and nighttime temperatures must be >5 °C / >41 °F when working with this product.



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:

Phone: +353 46 9432104

Fax: +353 46 9432435

info@ecologicalbuildingsystems.com

For Stockists contact

Ireland

Phone: +353 (0)46 9432104

Fax: +353 (0)46 9432435

UK

Phone: +44 (0)1228 711 511

Fax: +44 (0)1228 712 280

Ecological Building Systems

info@ecologicalbuildingsystems.com

www.ecologicalbuildingsystems.com

MOLL bauökologische Produkte GmbH

Rheintalstraße 35 - 43

68723 Schwetzingen

Germany

www.proclima.com

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland