

SOLITEX FRONTA® QUATTRO

Breather membrane (WRB) for open-jointed cladding, gap width up to 35 mm



Technical data

		Material
Protective and covering fleece		Polypropylene microfibre
Functional film		Monolithic TEEE

Property	Regulation	Value
Colour		Black
Surface weight	BS EN 1849-2	180 g/m ²
Thickness	BS EN 1849-2	0.60 mm
Water vapour resistance factor μ	BS EN ISO 12572	80
sd value	BS EN ISO 12572	0.05 m
g value	BS EN ISO 12572	0.25 MN-s/g
Reaction to fire classification	BS EN 13501-1	E
Outdoor exposure		6 months
Watertight joints with 'connect' adhesive strips or TESCON tape	BS EN 13859-1	W1
Water column	BS EN ISO 811	10 000 mm
Watertightness, non-aged/aged*	BS EN 13859-2	W1 / W1
Tensile strength MD/CD	BS EN 13859-2 (A)	290 N/5 cm / 220 N/5 cm
Tensile strength MD/CD, aged*	BS EN 13859-2 (A)	200 N/5 cm / 135 N/5 cm
Elongation MD/CD	BS EN 13859-2 (A)	50% / 70%
Elongation MD/CD, aged*	BS EN 13859-2 (A)	30% / 40%
Nail tear-resistance MD/CD	BS EN 13859-2 (B)	220 N / 300 N
*) Durability after artificial ageing	BS EN 1297 / BS EN 1296	Passed (for walls with open joints)
Flexibility at low temperature	BS EN 1109	-40 °C ; -40 °F
Temperature resistance	EN 1109, EN 1296, EN 1297	Permanent -40 °C to 100 °C ; -40 °F to 212 °F
Thermal conductivity		0.04 W/(m·K)
Resistance to alkalis	BS EN 1847	Passed
CE labelling	BS EN 13859-2	Yes

Areas of application

For use as a breather membrane (weather-resistive barrier, WRB) behind closed and open facades (open-jointed cladding up to a gap width of 35 mm; cladding width = at least 3 x gap width). Installation onto boarding, wood-based panels and all mat or panel-shaped thermal insulation materials.

Supply forms

Art. no.	Length	Width	Contents	Weight	Sales unit	Container	GTIN
12933	50 m	1.5 m	75 m ²	13.5 kg	1	20	4026639129338
13729	50 m	3 m	150 m ²	27 kg	1	20	4026639137296

Advantages

- ✓ Well-protected building structures: highly permeable and, at the same time, maximum protection against driving rain
- ✓ Dry building structures: pore-free TEEE functional film actively transports moisture to the outside
- ✓ Not visible behind open-jointed cladding: black fleece with printed marking only in the overlap area
- ✓ Highest possible durability and thermostability thanks to the TEEE functional film
- ✓ 6 months of outdoor exposure


General conditions

SOLITEX FRONTA QUATTRO membranes should be installed with the black side facing outwards. The membranes are to be installed horizontally in a taut manner with no sagging.

When the product is used behind open-jointed cladding, the gap may be a maximum of 35 mm. The width of cladding pieces must be at least three times the gap width. The distance between the open-jointed cladding and the membrane must be at least 20 mm.

Fasteners may not be applied in areas where water run-off is collected.

Additional measures (e.g. covering with tarpaulins) should be taken during the construction phase in the case of buildings that are lived in or buildings that are to be given particular protection. Covering with tarpaulins should also be considered if construction work is to be interrupted for a longer period.



The applications and conditions described here are based on current research findings and practical experience. We reserve the right to change the recommended application designs and installation methods and to develop and thus change the properties and quality of individual products. We would be glad to inform you about the current state of engineering knowledge at the time that your installation is carried out.

The planning documentation that is available from pro clima provides further information about installation methods and design details. If you have questions, please contact pro clima Technical Support in Ireland and the UK:
Phone: +353 46 9432104
info@ecologicalbuildingsystems.com

To find your local stockist, please contact:

Ireland
Phone: +353 46 9432104

UK
Phone: +44 1228 711 511

Ecological Building Systems
info@ecologicalbuildingsystems.com
www.ecologicalbuildingsystems.com

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
68723 Schwetzingen
Germany
www.proclima.com

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland