SOLITEX FRONTA® HUMIDA

Breather membrane (WRB) for use behind ventilated pre-wall shells



Technical data

	Material
Protective and covering fleece	Polypropylene microfibre
Functional film	Monolithic polymer mixture

Property	Regulation	Value
Colour		Anthracite
Surface weight	BS EN 1849-2	115 g/m²
Thickness	BS EN 1849-2	0.40 mm
Water vapour resistance factor μ	BS EN 1931	1 250
sd value	BS EN 1931	0.50 m
g value	BS EN 1931	2.5 MNs/g
Reaction to fire classification	BS EN 13501-1	E
Outdoor exposure		3 months
Water column	BS EN ISO 811	10 000 mm
Watertightness, non-aged/aged*	BS EN 13859-2	W1 / W1
Tensile strength MD/CD	BS EN 13859-2 (A)	220 N/5 cm / 150 N/5 cm
Tensile strength MD/CD, aged*	BS EN 13859-2 (A)	240 N/5 cm / 155 N/5 cm
Elongation MD/CD	BS EN 13859-2 (A)	85% / 85%
Elongation MD/CD, aged*	BS EN 13859-2 (A)	60% / 60%
Nail tear-resistance MD/CD	BS EN 13859-2 (B)	125 N / 150 N
*) Durability after artificial ageing	BS EN 1297 / BS EN 1296	Passed
Flexibility at low temperature	BS EN 1109	-40 °C ; -40 °F
Temperature resistance, permanent	EN 1109, EN 1296, EN 1297	-40 °C to 100 °C
Thermal conductivity		0.04 W/(m·K)
CE labelling	BS EN 13859-2	Yes

Areas of application

For use as a slightly diffusion-inhibiting breather membrane (weather-resistive barrier, WRB) on mineral-fibre and wood-fibre insulating panels behind a ventilated masonry/brick exterior wall.

Supply forms

Art. no.	Length	Width	Contents	Weight	Sales unit	Container	GTIN
14006	50 m	1.5 m	75 m²	9 kg	1	20	4026639140067
14069	50 m	3 m	150 m²	18 kg	1	20	4026639140692

Advantages

- ✔ In accordance with DIN 68800-2: for timber wall structures behind ventilated pre-wall shells
- ✔ Protects wall structures against moisture from the ventilation layer
- ✔ Protects the building structure during the construction phase: very resistant to driving rain
- ✔ 3 months of outdoor exposure

General conditions

SOLITEX FRONTA HUMIDA membranes must be installed with the printed side facing outwards. The membranes are to be installed horizontally in a taut manner with no sagging.

Fasteners should not be applied in areas where water run-off is collected.

Additional measures (e.g. covering with tarpaulins) should be taken during the construction phase in the case of buildings that are lived in or buildings that are to be given particular protection. Covering with tarpaulins should also be considered if construction work is to be interrupted for a longer period.

The applications and conditions described here are based on current research findings and practical experience. We reserve the right to change the recommended application designs and installation methods and to develop and thus change the properties and quality of individual products. We would be glad to inform you about the current state of engineering knowledge at the time that your installation is carried out.

The planning documentation that is available from pro clima provides further information about installation methods and design details. If you have questions, please contact pro clima Technical Support in Ireland and the UK:
Phone: +353 46 9432104
info@ecologicalbuildingsystems.com

To find your local stockist, please contact:

Ireland
Phone: +353 46 9432104

UK
Phone: +44 1228 711 511

Ecological Building Systems
info@ecologicalbuildingsystems.com
www.ecologicalbuildingsystems.com

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
68723 Schwetzingen
Germany
www.proclima.com

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.

Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104

Email us

info@ecologicalbuildingsystems.com

Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland

ecological BUILDING SYSTEMS

Discover our solutions online at

ecologicalbuildingsystems.com