

## Double-sided adhesive tape for interior and exterior use



## Technical data

	Material	
Adhesive	Special acrylate adhesive	
Release film	Silicone-coated PE film	
Reinforcement	Plastic	

Property	Regulation	Value
Colour		Transparent
Bond durability, non-aged/ aged	DIN 4108-11 / EN 17990	Passed
Application temperature		Above -10 °C ; 14 °F
Temperature resistance		Permanent -40 °C to 90 °C ; -40 °F to 194 °F
Storage		Cool and dry

# Areas of application

Exterior use: Moisture-resistant sticking of overlaps between underlay and breather (WRB) membranes and of on-roof vapour control and airtight membranes onto hard surfaces.

Interior use: Fixing vapour control and airtight membranes onto metal structures. Also for joints to windows, for example.

## Supply form

Art. no.	Length	Width	Weight	Sales unit	Container	GTIN
1AR03071	80 m	25 mm	0.66 kg	10	1200	4026639230713
1AR02983	80 m	40 mm	1.02 kg	6	720	4026639229830

#### Advantages

- ✓ Good component reliability thanks to permanently sealed adhesive joints
- ✓ Construction in adherence with standards: for airtight sealing in accordance with DIN 4108-7, SIA 180 and RE 2020
- ✓ Excellent values in hazardous substance testing, has been tested according to the ISO 16000 evaluation scheme

# Substrates

Clean subsurfaces before applying tape. Adhesion is not possible on frozen surfaces. There must be no water-repellent substances (e.g. grease or silicone) on surfaces where adhesives are to be applied. Subsurfaces must be sufficiently dry and stable.

Permanent adhesion is achieved on all pro clima interior and exterior membranes, on other vapour control and airtight membranes (e.g. those made of PE, PA, PP and aluminium) and on other underlay and breather (WRB) membranes (e.g. those made of PP and PET). Adhesive bonds are possible with planed and painted wood, hard plastics and metal (e.g. pipes, windows etc.) and hard wood-based panels (chipboard, OSB and plywood panels).

The best results in terms of reliability are achieved on high-quality subsurfaces. It is your responsibility to check the suitability of the subsurface; adhesion tests may be necessary in certain cases. Pre-treatment with TESCON PRIMER is recommended in the case of subsurfaces that have insufficient stability.

# General conditions

Stuck joints must not be subjected to tensile forces. Rub the adhesive tapes firmly to secure the adhesive bonds. Ensure that there is sufficient resistance pressure. Windproof, airtight or rainproof sealing can only be achieved on vapour control or underlay/facade membranes that have been installed without folds or creases. Ventilate continuously and systematically to prevent build-up of excessive humidity; use a dryer if necessary.



Tested for hazardous substances according to





The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and

Phone: +353 46 9432104 Fax: +353 46 9432435

info@ecologicalbuildingsystems.com

#### For Stockists contact

#### Ireland

Phone: +353 (0)46 9432104 Fax: +353 (0)46 9432435

UK

Phone: +44 (0)1228 711 511 Fax: +44 (0)1228 712 280

## **Ecological Building Systems**

info@ecologicalbuildingsystems.com www.ecologicalbuildingsystems.com

## MOLL bauökologische Produkte GmbH

Rheintalstraße 35 - 43 68723 Schwetzingen Germany www.proclima.com



For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



## Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



## Email us

info@ecologicalbuildingsystems.com



## Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland

