# Application gun for AEROSANA system foil cartridges



# Technical data

	iviateriai				
Main component	Stable aluminium pressure cylinder, ergonomic nylon handle				
Property	Regulation	Value			
Length		445 mm ; 17 1/2"			
Width		276 mm ; 10 7/8"			
Height		83 mm ; 3 1/4"			
Weight		1.6 kg ; 3.53 lbs			

# Areas of application

For particularly quick and easy application of the AEROSANA VISCONN and AEROSANA VISCONN FIBRE sealants from 600 ml foil cartridges onto smooth and rough mineral and non-mineral subsurfaces such as timber, wood fibreboards, OSB, stone, plaster, concrete etc.

For use with air compressors capable of up to 6.8 bar (100 psi), 300 l/min air flow.

# Supply form

Art. no.	Length	Width	Height	Weight	GTIN
1AR02714	445 mm	276 mm	276 mm	1.6 kg	4026639227140

# Advantages

- $\begin{tabular}{ll} \checkmark & Work more quickly: application and spreading of liquid sealant in a single working step \\ \end{tabular}$
- ✓ Precise application of sealant: setting 1 for a line of sealant to fill joints, setting 2 to spray over and seal surfaces
- ✓ Allows the technician to work with one hand
- ✓ No brush required
- ✓ Pressure: up to 6.8 bar (100 psi)

# General conditions

The AEROFIXX device is connected to a compressor with a suction flow rate of >300 l/min. The pressure should be set to 6 bar. All AEROSANA VISCONN variants in 600 ml foil cartridges can be applied using the AEROFIXX device. You can easily switch between line (bead) application and spray application by turning the spray head.





### Data sheet AEROFIXX

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:

Phone: +353 46 9432104 Fax: +353 46 9432435

info@ecologicalbuildingsystems.com

### For Stockists contact

#### Ireland

Phone: +353 (0)46 9432104 Fax: +353 (0)46 9432435

UK

Phone: +44 (0)1228 711 511 Fax: +44 (0)1228 712 280

# **Ecological Building Systems**

info@ecologicalbuildingsystems.com www.ecologicalbuildingsystems.com

# MOLL bauökologische Produkte GmbH

Rheintalstraße 35 - 43 68723 Schwetzingen Germany www.proclima.com



For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



# Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



# Email us

info@ecologicalbuildingsystems.com



# Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland

