AEROFIXX

Application gun for AEROSANA system foil cartridges

Technical data

	Material
Main component	Stable aluminium pressure cylinder, ergonomic nylon handle

Property	Regulation	Value
Length		445 mm ; 17½"
Width		276 mm ; 10⅞"
Height		83 mm ; 3¼"
Weight		1.6 kg ; 3.53 lbs

Areas of application

For particularly quick and easy application of the AEROSANA VISCONN and AEROSANA VISCONN FIBRE sealants from 600 ml foil cartridges onto smooth and rough mineral and non-mineral subsurfaces such as timber, wood fibreboards, OSB, stone, plaster, concrete etc.

For use with air compressors capable of up to 6.8 bar (100 psi), 300 l/min air flow.

Supply forms

Art. no.	Length	Width	Height	Weight	GTIN
1AR02714	445 mm	276 mm	276 mm	1.6 kg	4026639227140

Advantages

- ✔ Work more quickly: application and spreading of liquid sealant in a single working step
- ✔ Precise application of sealant: setting 1 for a line of sealant to fill joints, setting 2 to spray over and seal surfaces
- ✔ Allows the technician to work with one hand
- ✔ No brush required
- ✔ Pressure: up to 6.8 bar (100 psi)

General conditions

The AEROFIXX device is connected to a compressor with a suction flow rate of >300 l/min. The pressure should be set to 6 bar. All AEROSANA VISCONN variants in 600 ml foil cartridges can be applied using the AEROFIXX device. You can easily switch between line (bead) application and spray application by turning the spray head.

Made in Germany developed and produced by pro clima

The applications and conditions described here are based on current research findings and practical experience. We reserve the right to change the recommended application designs and installation methods and to develop and thus change the properties and quality of individual products. We would be glad to inform you about the current state of engineering knowledge at the time that your installation is carried out.

The planning documentation that is available from pro clima provides further information about installation methods and design details. If you have questions, please contact pro clima Technical Support in Ireland and the UK:
Phone: +353 46 9432104
info@ecologicalbuildingsystems.com

To find your local stockist, please contact:

Ireland
Phone: +353 46 9432104

UK
Phone: +44 1228 711 511

Ecological Building Systems
info@ecologicalbuildingsystems.com
www.ecologicalbuildingsystems.com

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
68723 Schwetzingen
Germany
www.proclima.com

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.

Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104

Email us

info@ecologicalbuildingsystems.com

Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland

ecological BUILDING SYSTEMS

Discover our solutions online at

ecologicalbuildingsystems.com