

SOLITEX FRONTA® QUATTRO FB

Flame-resistant breather membrane (WRB) for open-jointed cladding, gap width up to 35 mm, with self-adhesive strips



Technical data

Material		
Protective and covering fleece	Polypropylene microfibre	
Property	Regulation	Value
Colour		Black
Surface weight	BS EN 1849-2	145 g/m ²
Thickness	BS EN 1849-2	0.50 mm
Water vapour resistance factor μ	BS EN ISO 12572	160
sd value	BS EN ISO 12572	0,08 m
g value		0.4 MN·s/g
Reaction to fire classification	BS EN 13501-1	B-s1, d0
Outdoor exposure		6 months
Watertight joints with 'connect' adhesive strips or TESCON tape	BS EN 13859-1	W1
Water column	BS EN ISO 811	10 000 mm
Watertightness, non-aged/aged*	BS EN 13859-2	W1 / W1
Tensile strength MD/CD	BS EN 13859-2 (A)	260 N/5 cm / 225 N/5 cm
Tensile strength MD/CD, aged*	BS EN 13859-2 (A)	260 N/5 cm / 220 N/5 cm
Elongation MD/CD	BS EN 13859-2 (A)	60 % / 80 %
Elongation MD/CD, aged*	BS EN 13859-2 (A)	30% / 40%
Nail tear-resistance MD/CD	BS EN 13859-2 (B)	190 N / 220 N
*) Durability after artificial ageing	BS EN 1297 / BS EN 1296	Passed (for walls with open joints)
Flexibility at low temperature	BS EN 1109	-40 °C ; -40 °F
'connect' adhesion		Above +0 °C
Temperature resistance	EN 1109, EN 1296, EN 1297	Permanent -40 °C to 80 °C ; -40 °F to 176 °F
Thermal conductivity		0.04 W/(m·K)
CE labelling	BS EN 13859-2	Yes

Areas of application

For use as a breather membrane (weather-resistant barrier, WRB) behind closed and open facades (open-jointed cladding up to a gap width of 35 mm; cladding width = at least 3 x gap width). Installation onto boarding, wood-based panels and all mat or panel-shaped thermal insulation materials.

Supply form

Art. no.	Length	Width	Contents	Weight	Sales unit	Container	GTIN
1AR02725	50 m	1.5 m	75 m ²	12 kg	1	20	4026639227256

Advantages

- ✓ Improved safety: 'not easily flammable', reaction to fire classification B-s1, d0 as per EN 13501-1
- ✓ Well-protected building structures: highly permeable and, at the same time, maximum protection against driving rain
- ✓ Not visible behind open-jointed cladding: black fleece with printed marking only in the overlap area
- ✓ Highest possible durability and thermostability thanks to the monolithic functional film
- ✓ 6 months of outdoor exposure
- ✓ Quick and reliable sealing thanks to the integrated 'connect' self-adhesive strips on the long strips of the membrane

General conditions

SOLITEX FRONTA QUATTRO FB membranes should be installed with the black side facing outwards. The membranes are to be installed horizontally in a taut manner with no sagging.



When the product is used behind open-jointed cladding, the gap may be a maximum of 35 mm. The width of cladding pieces must be at least three times the gap width. The distance between the open-jointed cladding and the membrane must be at least 20 mm.

Fasteners may not be applied in areas where water run-off is collected.

Additional measures (e.g. covering with tarpaulins) should be taken during the construction phase in the case of buildings that are lived in or buildings that are to be given particular protection. Covering with tarpaulins should also be considered if construction work is to be interrupted for a longer period.



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:
Phone: +353 46 9432104
Fax: +353 46 9432435
info@ecologicalbuildingsystems.com

For Stockists contact

Ireland

Phone: +353 (0)46 9432104
Fax: +353 (0)46 9432435

UK

Phone: +44 (0)1228 711 511
Fax: +44 (0)1228 712 280

Ecological Building Systems

info@ecologicalbuildingsystems.com
www.ecologicalbuildingsystems.com

MOLL bauökologische Produkte GmbH

Rheintalstraße 35 - 43
68723 Schwetzingen
Germany
www.proclima.com

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland