KAFLEX post

Cable grommet for retrofit installation, Ø up to 20 mm, for interior and exterior use

Technical data

	Material
Backing	Special PP fleece / perforated PE foil
Adhesive	Water-resistant SOLID adhesive
Release film	Silicone-coated paper

Property	Regulation	Value
Colour		Dark blue
Outdoor exposure		3 months
Bond durability, non-aged/aged	BS EN 17990	Passed
Application temperature		Above -10 °C ; 14 °F
Temperature resistance, permanent		-40 °C to 90 °C
Storage		Cool and dry
Passive House Certification	Passivhaus Institut	phA

Areas of application

For quick, permanently secure sealing of previously installed cables and conduits up to 20 mm in the internal airtightness layer. As a result of its water-resistant adhesive and substrate materials, KAFLEX post is also suitable for exterior use (e.g. windtightness in underlay and facade area).

Supply forms

Art. no.	Length	Width	Contents	Weight	GTIN
1AR02187	140 mm	140 mm	10 pieces	0.3 kg	4026639221872

Advantages

- ✔ Keeps building structures dry: practical joints to already installed cables
- ✔ Easy to work with: extremely flexible and elastic
- ✔ Reliable joints thanks to water-resistant SOLID adhesive
- ✔ Standards-compliant construction: for airtight sealing in accordance with DIN 4108-7, SIA 180 and RE 2020
- ✔ 3 months of outdoor exposure
- ✔ Excellent values in hazardous substance testing, has been tested according to the ISO 16000 evaluation scheme

Substrates

Clean subsurfaces before sticking. Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on surfaces where adhesives are to be applied. Subsurfaces must be sufficiently dry and stable; if necessary, subsurfaces should be stabilised or renewed.

Install the cables without strain, fix cables with a cable clip as required.

A permanent bond is achieved on all pro clima indoor and outdoor membranes, other vapour control and airtight membranes (e.g. PE, PA, PP and aluminium foil) as well as roof and breather (WRB) membranes (e.g. PP and PET).

Adhesive bonds are possible on planed and painted wood, hard plastics and metal (e.g. pipes, windows etc.), hard wood-based panels (chipboard, OSB, plywood, MDF and wood-fibre underlay panels).

Pre-treatment with TESCON PRIMER is required in the case of adhesion to wood-fibre underlay panels or on smooth, mineral subsurfaces.

The best results in terms of reliability are achieved on high-quality subsurfaces. Particular care is necessary when working with older or multi-layer subsurfaces. It is your responsibility to check the suitability of the subsurface; adhesion tests may be necessary in certain cases. Pre-treatment of the subsurface with TESCON PRIMER will improve the adhesive bond.

General conditions

The adhesive bonds should not be subjected to tensile strain. Rub the adhesive tapes firmly to secure the adhesive bonds. Ensure that there is sufficient resistance pressure.

Windproof, airtight or rainproof sealing can only be achieved on vapour control membranes, roofing underlays or breather (WRB) membranes that have been laid without folds or creases. Ventilate continuously and systematically to prevent the build-up of excessive humidity; use a dryer if necessary.

pro clima®

CERTIFIED COMPONENT
Passive House Institute

ÉMISSIONS DANS L'AIR INTÉRIEUR*
A+
A+ A B C
*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes missions)

Tested for hazardous substances according to ISO 16000

NSAI Agrément
pro clima Intelligent Airtight System
CERT No. 07/0297

The applications and conditions described here are based on current research findings and practical experience. We reserve the right to change the recommended application designs and installation methods and to develop and thus change the properties and quality of individual products. We would be glad to inform you about the current state of engineering knowledge at the time that your installation is carried out.

The planning documentation that is available from pro clima provides further information about installation methods and design details. If you have questions, please contact pro clima Technical Support in Ireland and the UK:
Phone: +353 46 9432104
info@ecologicalbuildingsystems.com

To find your local stockist, please contact:

Ireland
Phone: +353 46 9432104

UK
Phone: +44 1228 711 511

Ecological Building Systems
info@ecologicalbuildingsystems.com
www.ecologicalbuildingsystems.com

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
68723 Schwetzingen
Germany
www.proclima.com

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.

Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104

Email us

info@ecologicalbuildingsystems.com

Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland

ecological BUILDING SYSTEMS

Discover our solutions online at

ecologicalbuildingsystems.com