

Installation instructions

CONTEGA® SOLIDO EXO-D

Sub-sill on timber projects



1. Prepare the window opening

Preparatory step for window installation on timber construction projects

Tape and seal the structure surface, window reveals and all joints so that they are airtight and watertight against driving rain.



2. Side details

In the case of reveal plates or a rear-ventilated structure, allow EXTOSEAL ENCORS to run approx. 10 to 15 cm up each reveal side. If the reveal surfaces are to be plastered, run the sill tape up approx. 6 cm or else to the upper edge of the window sill profile.



3. Apply tape to the sill surface

Apply EXTOSEAL ENCORS to the sill surface, extending it at least as far as the inner edge of the window profile or – if necessary – across the entire depth of the structure. Allow an excess of at least 2 cm on the outside, or else as far as a suitable drip profile.

A sloped wall surface under the window will drain off water.



4. Extend the sub-sill to the outside

In the case of a rear-ventilated facade, stretch the tape in the corners (without damaging it) and stick it to a suitable subsurface, e.g. SOLITEX FRONTA WA. Rub EXTOSEAL ENCORS using the PRESSFIX tool to secure the adhesive bond.

Sub-sill on masonry and concrete projects



1. Apply a smooth plaster finish to the window opening

Preparatory step for window installation on masonry and concrete construction projects

Apply a smooth plaster finish to the side and bottom areas where seals are to be installed.

If a plaster finish or sealing filler is applied to the wall area under the window, the transition to the side reveals can be sealed with EXTOSEAL ENCORS to cover any possible cracks (capillary gaps).

A sloped wall surface under the window will drain off water.



2. Side details

If the reveal surfaces are to be plastered, allow EXTOSEAL ENCORS to run approx. 6 cm up each reveal side or else to the upper edge of the window sill profile.

In the case of reveal plates or a rear-ventilated structure, allow approx. 10 to 15 cm here.



3. Apply tape to the sill surface

Apply EXTOSEAL ENCORS to the sill surface, extending it at least as far as the inner edge of the window profile or – if necessary – across the entire depth of the structure.

Stick the excess tape on the outside to a suitable drip profile.

Installation steps for window-sealing



1. Window to be mounted into a timber, masonry or timber structure

CONTEGA SOLIDO EXO-D is to be pre-installed before the window is mounted. The frame is laid out flat with the exterior side of the frame facing up. The open ends of the window profile have been filled and the filling/sealing profiles have been attached.



3. Create corner folds

Create corner folds as shown here to make it easier to create a reliable seal to the window reveal at the corners later on. The size of the corner folds should correspond to around 1.5 times the joint width.



5. Install the window and insulate the joint

Fold in the CONTEGA SOLIDO EXO-D tape so that it is not in the way, and then mount the window using a suitable fastening system. Fill in the joint with a suitable insulation material, leaving no cavities.



2. Start applying tape at the top of the frame

Remove the single release film strip on the printed side, position the tape on the side of the frame and then gradually stick in place. The printed side of the tape will face the window and extends upwards. Rub using the PRESSFIX application tool to secure the adhesive bond. If tape application is started at the side of the window frame, ensure that the tape overlap is executed in a waterproof manner.



4. Stick the tape all around the window frame

Stick the tape all around the side of the frame. At the end, cut off any excess length. Remove the release films from the end of the tape that is already in place in the overlap area, and stick the ends of the tape to create the overlap. Ensure that an uninterrupted rainproof seal is created when installing the tape. Rub using the PRESSFIX application tool to secure the adhesive bond.



6. Stick the tape to the reveal all around the frame and rub to secure

Remove the release film and gradually stick the tape to the reveal all around the window frame, allowing slack to accommodate relative motion between components. Ensure that there is an uninterrupted rainproof seal when applying the tape. Rub using the PRESSFIX application tool to secure the adhesive bond.



Tip

For the joint at bottom of the window, application of CONTEGA SOLIDO EXO-D can be continued onto the front face of the sill connection profile. This makes it easier to mount the window and apply the tape to the sub-sill later. In this case, a length of tape must be applied over the corner fold. This can also be done with all other corner folds. Tape should only be applied onto surfaces that will not be visible in the long term.

Substrates

Clean subsurfaces before sticking. Uneven mineral subsurfaces may need to be levelled with a smooth plaster finish. Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on surfaces where adhesives are to be applied.

Observe the recommendations for plastering over adhesive tapes that are specified by the producer of the plaster. In most cases, it is recommended that the width of adhesive tape that is to be plastered over should not exceed 60 mm (2 5/8") or 50% of the reveal area. Subsurfaces must be sufficiently dry and stable.

Permanent adhesion is achieved on all pro clima exterior membranes and on other underlay and breather (WRB) membranes (e.g. those made of PP and PET). Tapes can be applied to planed or painted wood, hard plastics, hard wood-based panels (chipboard, OSB and plywood panels). For sealing joints on masonry or concrete or on rough substrates, use ORCON F.

The best results in terms of structural stability are achieved on high-quality subsurfaces. It is your responsibility to check the suitability of the subsurface; adhesion tests may be necessary in certain cases. Pre-treatment with TESCON PRIMER is recommended in the case of subsurfaces with insufficient stability.

General conditions

Taped joints must not be subjected to tensile forces.

Rub the adhesive tapes firmly to secure the adhesive bonds. Ensure that there is sufficient resistance pressure.

Seals that are windproof and resistant to driving rain can only be achieved if the sealing tape is installed free of folds and breaks.

When plastering, please observe the recommendations of the plaster manufacturer for non-absorbent subsurfaces. A bonding course may be necessary.

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about installation and design details is available in the pro clima planning documentation. If you have any questions, please contact [pro clima Technical Support] (<https://proclima.com/service/technical-support>).

MOLL
bauökologische Produkte GmbH
 Rheintalstraße 35 - 43
 D-68723 Schwetzingen
 Fon: +49 (0) 62 02 - 27 82.0
 eMail: info@proclima.de

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland