STOPPA

Airtight plugs for ducts for interior and exterior use



Technical data

Material	
Main component	Thermoplastic elastomer (TPE)

Property	Regulation	Value
Colour		Blue
Application temperature		> -10 °C ; 14 °F
Temperature resistance, permanent		-50 °C to 90 °C
Storage		Cool and dry

Areas of application

For the quick and lasting, secure airtight installation of cables in ducts. Conduit grommets (e.g. ROFLEX Ø 15-30 mm) are available for the airtight connection of ducts to the vapour control and airtight membrane.

Supply forms

Art. no.	For ⌀ pipe	Contents	Weight	GTIN
12945	o.d. 16 mm | i.d. 11 mm	20 pieces	0.1 kg	4026639129451
12947	o.d. 20 mm | i.d. 15 mm	20 pieces	0.13 kg	4026639129475
12949	o.d. 25 mm | i.d. 19.5 mm	20 pieces	0.13 kg	4026639129499
12951	o.d. 32 mm | i.d. 25 mm	20 pieces	0.2 kg	4026639129512
12953	o.d. 40 mm | i.d. 31.5 mm	20 pieces	0.2 kg	4026639129536

Advantages

- ✔ Ensures cables in ducts are sealed
- ✔ Standards-compliant construction: for airtight sealing in accordance with DIN 4108-7, SIA 180 and RE 2020
- ✔ Simple insertion: press-out membrane creates a reliable seal with cable
- ✔ Easy to work with: holes can be pre-formed with a nail or nozzle tip
- ✔ Also suitable for several cables
- ✔ Reliable air sealing to profiled pipes thanks to multiple lip sealing
- ✔ Can be easily removed if a new cable is to be installed
- ✔ Excellent values in hazardous substance testing, has been tested according to the ISO 16000 evaluation scheme

ÉMISSIONS DANS L'AIR INTÉRIEUR* A+ A+ A B C

*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes missions)

Tested for hazardous substances according to ISO 16000

Made in Germany developed and produced by pro clima

The applications and conditions described here are based on current research findings and practical experience. We reserve the right to change the recommended application designs and installation methods and to develop and thus change the properties and quality of individual products. We would be glad to inform you about the current state of engineering knowledge at the time that your installation is carried out.

The planning documentation that is available from pro clima provides further information about installation methods and design details. If you have questions, please contact pro clima Technical Support in Ireland and the UK:
Phone: +353 46 9432104
info@ecologicalbuildingsystems.com

To find your local stockist, please contact:

Ireland
Phone: +353 46 9432104

UK
Phone: +44 1228 711 511

Ecological Building Systems
info@ecologicalbuildingsystems.com
www.ecologicalbuildingsystems.com

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
68723 Schwetzingen
Germany
www.proclima.com

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.

Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104

Email us

info@ecologicalbuildingsystems.com

Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland

ecological BUILDING SYSTEMS

Discover our solutions online at

ecologicalbuildingsystems.com