Airtight plugs for ducts for interior and exterior use



Technical data

	Mater	ial			
Main component	Thermoplastic elastomer (TPE)				
Property	Regulation	Value			
Colour		Blue			
Application temperature		> -10 °C ; 14 °F			
Temperature resistance		Permanent -50 °C to 90 °C ; -58 °F to 194 °F			
Storage		Cool and dry			

Areas of application

For the quick and lasting, secure airtight installation of cables in ducts. Conduit grommets (e.g. ROFLEX Ø 15-30 mm) are available for the airtight connection of ducts to the vapour control and airtight membrane.

Supply form

Art. no.	Pipe diameter	Contents	Weight	GTIN
12945	o.d. 16 mm i.d. 11 mm	20 pieces	0.1 kg	4026639129451
12947	o.d. 20 mm i.d. 15 mm	20 pieces	0.13 kg	4026639129475
12949	o.d. 25 mm i.d. 19.5 mm	20 pieces	0.13 kg	4026639129499
12951	o.d. 32 mm i.d. 25 mm	20 pieces	0.2 kg	4026639129512
12953	o.d. 40 mm i.d. 31.5 mm	20 pieces	0.2 kg	4026639129536

Advantages

- ✓ Ensures cables in ducts are sealed
- ✓ Construction in adherence with standards: for airtight sealing in accordance with DIN 4108-7, SIA 180 and RE 2020
- ✓ Simply insertion: press-out membrane creates a reliable seal with cable
- ✓ Easy to work with: holes can be pre-formed with a nail or nozzle tip
- ✓ Also suitable for several cables
- ✓ Reliable air sealing to profiled pipes thanks to multiple lip sealing
- ✓ Can be easily removed if a new cable is to be installed.
- Excellent values in hazardous substance testing, has been tested according to the ISO 16000 evaluation scheme



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes missions) Tested for hazardous substances according to 150 16000



Data sheet STOPPA

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:

Phone: +353 46 9432104 Fax: +353 46 9432435

info@ecologicalbuildingsystems.com

For Stockists contact

Ireland

Phone: +353 (0)46 9432104 Fax: +353 (0)46 9432435

UK

Phone: +44 (0)1228 711 511 Fax: +44 (0)1228 712 280

Ecological Building Systems

info@ecologicalbuildingsystems.com www.ecologicalbuildingsystems.com

MOLL bauökologische Produkte GmbH

Rheintalstraße 35 - 43 68723 Schwetzingen Germany www.proclima.com



For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland

