

DECLARATION OF PERFORMANCE CPR-130/2020 DP011EN21031202



1. Unique identification code of the product-type: **Aquabond.**
2. Intended uses: **Cementitious coating for intended use in concrete surface protection by moisture control and increasing resistivity methods.**
3. Manufacturer: **Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN) - www.diasen.com**
4. Systems of AVCP: **System 2+**
System 4 (for reaction to fire)
5. Harmonized standards: **EN 1504-2:2004.**
Notified bodies: **ABICert – No. 1982.**
6. Performances declared:

Essential characteristics	Performances
Water vapour permeability	$\mu = 1941$
Capillary absorption and permeability to water	NPD
Tensile adhesion strength after freeze-thaw cycles	NPD
Adhesion strength by pull-off test	NPD
Reaction to fire	NPD
Dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above..

Signed for and on behalf of the manufacturer by: **Diego Mingarelli (Legal Representative)**
Sassoferrato, 30/11/2020

DiaSen srl
 Z. Ind.le Berbentina, 5
 60041 Sassoferrato (AN)
 P. IVA/C.F. 01553210426

 1982	 Zona Industriale Berbentina, 5 – 60041 Sassoferrato (AN) – Italy www.diasen.com												
<p style="text-align: center;">20 CPR-130/2020 EN 1504-2 AQUABOND</p> <p style="text-align: center;"><i>Cementitious coating for intended use in concrete surface protection by moisture control and increasing resistivity methods</i></p>													
<table> <tr> <td>Water vapour permeability</td> <td style="text-align: right;">$\mu = 1941$</td> </tr> <tr> <td>Capillary absorption and permeability to water</td> <td style="text-align: right;">NPD</td> </tr> <tr> <td>Tensile adhesion strength after freeze-thaw cycles</td> <td style="text-align: right;">NPD</td> </tr> <tr> <td>Adhesion strength by pull-off test</td> <td style="text-align: right;">NPD</td> </tr> <tr> <td>Reaction to fire</td> <td style="text-align: right;">NPD</td> </tr> <tr> <td>Dangerous substances</td> <td style="text-align: right;">See SDS</td> </tr> </table>		Water vapour permeability	$\mu = 1941$	Capillary absorption and permeability to water	NPD	Tensile adhesion strength after freeze-thaw cycles	NPD	Adhesion strength by pull-off test	NPD	Reaction to fire	NPD	Dangerous substances	See SDS
Water vapour permeability	$\mu = 1941$												
Capillary absorption and permeability to water	NPD												
Tensile adhesion strength after freeze-thaw cycles	NPD												
Adhesion strength by pull-off test	NPD												
Reaction to fire	NPD												
Dangerous substances	See SDS												

DIASEN supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.

DIASEN srl

Zona Ind. Berbentina, 5 60041 Sassoferrato (AN) - ITALY
 Tel. +39 0732 9718 - Fax +39 0732 971899 - diasen@diasen.com - www.diasen.com

PARTITA IVA 01553210426 - R.E.A. Ancona n.150933
 Reg.Imp. Ancona 01553210426 - Cap. Soc. €400.000,00 i.v.



For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland